




## Allgemeine Information

### Technisch - Systeme

<b>Ean</b>	8021696192550
<b>Artikel</b>	FLUO WIDE 1800 3000K WH
<b>Installation</b>	Systeme
<b>Garantie</b>	5 years
<b>Bruttogewicht</b>	6.64 kg
<b>Volumen</b>	0.025675 m <sup>3</sup>

## Technische Information

<b>Nettogewicht</b>	4.42 kg
<b>Isolationsklasse</b>	I
<b>Schutzindex</b>	IP20
<b>Einhaltung</b>	CE
<b>Betriebstemperatur</b>	0° ~ +40 °C
<b>Dimmer</b>	NO, On-Off
<b>Leistung</b>	220-240 V AC 50/60 Hz
<b>Energieversorgung</b>	In-built, included Replaceable (by qualified operators only), electronic, osram
<b>einschließlich Zubehör</b>	Mounting kit (suspension, recessed, surface), Dimmable driver, Luminous corner, Structure connector



## Quellinfo

<b>Integrierte Quelle</b>	Integrated LED module
<b>Austauschbare Quelle</b>	Replaceable (by qualified operators only)
<b>Leistung</b>	36 W
<b>Emissionen</b>	Direct
<b>Maximaler Verbrauch</b>	max 36,00 W
<b>Merkmale LED</b>	LED SMD SAMSUNG
<b>CCT LED</b>	3000 K
<b>Dauer LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 80
<b>SDCM</b>	3
<b>Lichtstrahlwinkel</b>	105°
<b>Lichtstrahlfluss</b>	5050 lm
<b>Nützlicher Lichtstrom</b>	3700 lm