

## General info

## Lampadine e accessori - Strip led



|                     |  |
|---------------------|--|
| <b>Ean</b>          | 8021696346328                            |
| <b>Item</b>         | STRIP LED 120 SMD 05W/M 2700K CRI90 IP20 |
| <b>Installation</b> | -  |
| <b>Warranty</b>     | 5 years                                  |
| <b>Gross weight</b> | 0.11 kg                                  |
| <b>Volume</b>       | 0.000512 m <sup>3</sup>                  |

## Technical info

|                                 |                                 |
|---------------------------------|---------------------------------|
| <b>Net weight</b>               | 0.1 kg                          |
| <b>Insulation class</b>         | 3                               |
| <b>Compliance</b>               | CE                              |
| <b>Power output</b>             | 24 V DC                         |
| <b>Dimmer</b>                   | 1, Phase-cut                    |
| <b>Power supply</b>             | Required, remoted, not included |
| <b>Protection index</b>         | 20                              |
| <b>Lunghezza fornita</b>        | L 5000 x H 1 x P 8 mm           |
| <b>Accessories not included</b> | Remote driver                   |



## Source info

|                               |               |
|-------------------------------|---------------|
| <b>Power</b>                  | 25 W          |
| <b>Emission</b>               | Direct        |
| <b>Max consupation</b>        | max (1 m) 5 W |
| <b>CCT LED</b>                | 2700 K        |
| <b>Duration LED (t. 25°C)</b> | 50000 h       |
| <b>CRI</b>                    | > 90          |
| <b>SDCM</b>                   | 3             |
| <b>Light beam</b>             | 120 °         |
| <b>Useful light flux</b>      | (1 m) 430 lm  |
| <b>Photobiological risk</b>   | 1             |