


## General info

## Technical - Recessed lights



<b>Ean</b>	8021696193373
<b>Item</b>	BASIC FI ACCENT 20W 4000K
<b>Installation</b>	Recessed lights
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.77 kg
<b>Volume</b>	0.002673 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.66 kg
<b>Insulation class</b>	II
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Separate, included Replaceable (by qualified operators only), electronic, philips
<b>Recessed specifications</b>	Ø 125 - h. ≥ 110 , 5-20
<b>Load resistance</b>	IK02
<b>Front protection index</b>	IP44
<b>Accessories not included</b>	Dimmable driver

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	Replaceable (by qualified operators only)
<b>Power</b>	20 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 20,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°C)</b>	30000 h
<b>CRI</b>	> 80
<b>SDCM</b>	3
<b>Light beam</b>	52°
<b>Light beam flux</b>	2050 lm
<b>Useful light flux</b>	1910 lm
<b>Photobiological risk</b>	1