ideal lux.



Deva

General info

Technical - Systems

| Ean | 8021696332710 |
|--------------|-------------------------|
| Item | DEVA ACCENT 14W BK |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 0.25 kg |
| Volume | 0.000472 m ³ |

Technical info

| Net weight |
|--------------------------|
| Insulation class |
| Protection index |
| Compliance |
| Operating temperature |
| Dimmer |
| Power output |
| Power supply |
| Accessories not included |

0.23 kg Ш IP20 CE 0° ~ +40 °C [DO NOT COVER] Non-dimmable, On-Off 24 V DC Required, remoted, not included Deva profile

| | | 335 | | |
|----------|------------------|-----|-----------|-----|
| 00 00 | - <u>1</u> . 8 - | | • = .x. • | 101 |
| | • | 290 | • | 11 |

| Source | info |
|--------|------|
| | |

| Integrated course | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Repleaceable source | Replaceable (by qualified operators only) |
| Power | 14 W |
| Emission | Direct |
| Max consuption | max 14 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 30000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 34° |
| Light beam flux | 1400 lm |
| Useful light flux | 1130 lm |
| Photobiological risk | EXEMPT |