

General info


Technical - Recessed lights



| | |
|--------------|--------------------------|
| Ean | 8021696208596 |
| Item | DYNAMIC SOURCE 15W 4000K |
| Installation | Recessed lights |
| Guarantee | 5 years |
| Gross weight | 0.36 kg |
| Volume | 0.003044 m³ |

Technical info

| | |
|--------------------------|---|
| Net weight | 0.35 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic |
| Front protection index | IP54 |
| Accessories not included | Frame, Reflector, Narrow or wide beam lens, additional optic (Honeycomb or Elliptical), Dimmable driver |



Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 15 W |
| Emission | Direct |
| Max consupcion | max 15,00 W |
| Features LED | LED COB |
| CCT LED | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 35° |
| Light beam flux | 1650 lm |
| Useful light flux | 1350 lm |