
# ideal lux.





## Fox

### General info

#### **Technical - Spotlights and Tracks**

| Ean          | 8021696322339                 |
|--------------|-------------------------------|
| Item         | FOX 08W CRI90 4000K ON-OFF WH |
| Installation | Spotlights and Tracks         |
| Guarantee    | 5 years                       |
| Gross weight | 1 kg                          |
| Volume       | 0.001485 m³                   |

#### **Technical info**

| Net weight               | 0.3 kg   |
|--------------------------|--|
| Insulation class         | 1  |
| Protection index         | IP20   |
| Compliance               | CE   |
| Operating temperature    | 0° ~ +40 °C  |
| Dimmer                   | NO, On-Off   |
| Power output             | 220-240 V AC 50/60 Hz  |
| Power supply             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| Adjustability            | vert. 0°-90° , orizz. 0°-355°  |
| Accessories not included | Single connection on-off, Link on-off profile                                  |

#### Source info

| Integrated source      | Integr |
|------------------------|--------|
| Repleaceable source    | Repla  |
| Power                  | 8 W    |
| Emission               | Direct |
| Max consuption         | max 8  |
| Features LED           | LED (  |
| CCT LED                | 4000   |
| Duration LED (t. 25°c) | 30000  |
| CRI                    | > 90   |
| SDCM                   | 3      |
| Light beam             | 41°    |
| Light beam flux        | 950 lr |
| Useful light flux      | 810 lr |
|                        |        |

Integrated LED module Replaceable (by qualified operators only) 8 W Direct max 8,00 W LED COB BRIDGELUX 4000 K 30000 h > 90 3 41° 950 lm 810 lm