


## General info

## Technical - Recessed lights



<b>Ean</b>	8021696244181
<b>Item</b>	LED PANEL FI 4000K CRI90
<b>Installation</b>	Recessed lights
<b>Guarantee</b>	5 years
<b>Gross weight</b>	2.7 kg
<b>Volume</b>	0.014431 m <sup>3</sup>

## Technical info

<b>Net weight</b>	2.2 kg
<b>Insulation class</b>	II
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Separate, included Replaceable (by qualified operators only), electronic
<b>Accessories not included</b>	Dimmable driver, Mounting kit (Suspension kit, Surface kit, Plasterboard recessed frame)

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	Replaceable (by qualified operators only)
<b>Power</b>	40 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 40,00 W
<b>Features LED</b>	LED SMD
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°C)</b>	25000 h
<b>CRI</b>	> 90
<b>Light beam</b>	81°
<b>UGR Maximum</b>	< 19
<b>Light beam flux</b>	3800 lm
<b>Useful light flux</b>	3160 lm