# ideal lux.



## General info

#### **Technical - Recessed lights**



| Ean          | 8021696267876             |
|--------------|---------------------------|
| Item         | LIKA FI TRIM 12W 4000K WH |
| Installation | Recessed lights           |
| Guarantee    | 5 years                   |
| Gross weight | 0.41 kg                   |
| Volume       | 0.001292 m <sup>3</sup>   |

### **Technical info**

| Net weight               | 0.32 kg  |
|--------------------------|--|
| Insulation class         | Ш  |
| Protection index         | IP20   |
| Compliance               | CE   |
| Operating temperature    | 0° ~ +40 °C  |
| Dimmer                   | NO, On-Off   |
| Power output             | 220-240 V AC 50/60 Hz  |
| Power supply             | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |
| Recessed specifications  | 140 x 37 - h. ≥ 70 , 3-30  |
| Accessories not included | Dimmable driver  |

## Source info

| Integrated source      | Integrated LED module                     |
|------------------------|---|
| Repleaceable source    | Replaceable (by qualified operators only) |
| Power                  | 12 W                                      |
| Emission               | Direct                                    |
| Max consuption         | max 12,00 W                               |
| Features LED           | LED SMD OSRAM                             |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°c) | 50000 h                                   |
| CRI                    | > 90                                      |
| Light beam             | 29°                                       |
| UGR Maximum            | < 16                                      |
| Light beam flux        | 1250 lm                                   |
| Useful light flux      | 1130 lm                                   |
| Photobiological risk   | 2   |

