ideal lux.



General info

Technical - Recessed lights

Ean	8021696206233
Item	LIKA FI TRIM 20W 3000K WH
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.63 kg
Volume	0.001556 m³

Technical info

Net weight	0.48 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	273 x 37 - h. ≥ 70 , 3-30
Accessories not included	Dimmable driver



48

AAAAAAAAA

Source info

Integrated source	I
Repleaceable source	F
Power	2
Emission	0
Max consuption	r
Features LED	L
CCT LED	3
Duration LED (t. 25°c)	5
CRI	>
Light beam	2
UGR Maximum	~
Light beam flux	1
Useful light flux	1
Photobiological risk	2

Integrated LED module	
Replaceable (by qualified operators only)	
20 W	
Direct	
max 19,50 W	
LED SMD OSRAM	
3000 K	
50000 h	
> 90	
29°	
< 16	
1750 lm	
1550 lm	
2	