


General info

Technical - Recessed lights



| | |
|---------------------|-------------------------|
| Ean | 8021696327488 |
| Item | QUARK FI 3.0W 3000K WH |
| Installation | Recessed lights |
| Guarantee | 5 years |
| Gross weight | 0.1 kg |
| Volume | 0.000413 m ³ |

Technical info

| | |
|--------------------------------|--|
| Net weight | 0.07 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic |
| Recessed specifications | Ø 25 - h. ≥ 55 , 5-25 |

Source info

| | |
|-------------------------------|-----------------------|
| Integrated source | Integrated LED module |
| Replaceable source | No |
| Power | 3 W |
| Emission | Direct |
| Max consumption | max 3,00 W |
| Features LED | LED SMD BRIDGELUX |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 30000 h |
| CRI | > 90 |
| Light beam | 25° |
| Light beam flux | 250 lm |
| Useful light flux | 180 lm |
| Photobiological risk | 2 |