

## General info


## Technical - Recessed lights



<b>Ean</b>	8021696307756
<b>Item</b>	QUARK FI 5.0W 3000K WH
<b>Installation</b>	Recessed lights
<b>Warranty</b>	5 years
<b>Gross weight</b>	0.19 kg
<b>Volume</b>	0.000396 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.14 kg
<b>Insulation class</b>	II
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C [DO NOT COVER]
<b>Dimmer</b>	Non-dimmable, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Separate, included Replaceable (by qualified operators only), electronic



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	Replaceable (by qualified operators only)
<b>Power</b>	5 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 5 W
<b>Features LED</b>	LED SMD BRIDGELUX
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Light beam</b>	30°
<b>UGR Maximum</b>	< 19
<b>Light beam flux</b>	510 lm
<b>Useful light flux</b>	230 lm
<b>Photobiological risk</b>	2