

General info

Technical - Systems



| | |
|--------------|-------------------------|
| Ean | 8021696345017 |
| Item | STICK ACCENT 16W 2700K |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 0.25 kg |
| Volume | 0.000552 m ³ |

Technical info

| | |
|--------------------------|---------------------------------------|
| Net weight | 0.14 kg |
| Insulation class | III |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | 1, Phase-cut |
| Power output | 48 V DC |
| Power supply | Required, remoted, not included NO |
| Accessories not included | Stick profile |



Source info

| | |
|------------------------|-----------------------|
| Integrated source | Integrated LED module |
| Replaceable source | No |
| Power | 16 W |
| Emission | Direct |
| Max consumption | max 16 W |
| Features LED | LED SMD BRIDGELUX |
| CCT LED | 2700 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 40° |
| Light beam flux | 1650 lm |
| Useful light flux | 1160 lm |
| Photobiological risk | 1 |
| Standby power | < 0.50 W |