

General info


Technical - Systems



| | |
|--------------|------------------------|
| Ean | 8021696329512 |
| Item | STICK TRACK DOUBLE 06W |
| Installation | Systems |
| Guarantee | 5 years |
| Gross weight | 0.15 kg |
| Volume | 0.000593 m³ |

Technical info

| | |
|--------------------------|--|
| Net weight | 0.11 kg |
| Insulation class | III |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | 1, Phase-cut |
| Power output | 48 V DC |
| Power supply | Required, remoted, not included Replaceable (by qualified operators only) |
| Accessories not included | Stick profile |



Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 6 W |
| Emission | Direct |
| Max consupcion | max 6,00 W |
| Features LED | LED COB BRIDGELUX |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 30000 h |
| CRI | > 90 |
| Light beam | 24° |
| Light beam flux | 550 lm |
| Useful light flux | 380 lm |
| Photobiological risk | 1 |
| Standby power | < 0.50 W |