



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable non-dimmable projector with integrated LED sources and direct light emission

| | |
|----------------------|--|
| Ean | 8021696283944 |
| Articolo | FOX TR 3-PHASE 25W CRI80 3000K ON-OFF GD |
| Installazione | Proiettori e Binari |
| Garanzia | 5 years |
| Peso lordo | 0.64 kg |
| Volume | 0.002592 m ³ |

Info tecniche e installative

| | |
|--------------------------------|--|
| Peso netto | 0.54 kg |
| Classe di isolamento | I |
| Grado di protezione | IP20 |
| Conformità | CE |
| Temperatura d'esercizio | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Alimentazione | 220-240 V AC 50/60 Hz |
| Alimentatore | In-built, included Replaceable (by qualified operators only), electronic |
| Accessori non inclusi | Single connection on-off, Link 3-phase on-off profile |

Info sorgente e prestazionali

| | |
|------------------------------|---|
| Sorgente integrata | Integrated LED module |
| Sorgente sostituibile | Replaceable (by qualified operators only) |
| Potenza | 25 W |
| Emissione | Direct |
| Consumo massimo | max 25 W |
| Caratteristiche LED | LED COB |
| CCT LED | 3000 K |
| Durata LED (t. 25°c) | 50000 h |
| CRI | > 80 |
| SDCM | 3 |
| Fascio luminoso | 35° |
| Flusso sorgente | 3300 lm |
| Flusso utile | 2460 lm |
| Rischio fotobiologico | 1 |