


Info generali

Tecnico - Lampade da incasso


Indoor ceiling recessed lamp with integrated LED sources and direct light emission



Ean	8021696249728
Articolo	LED PANEL FI 4000K CRI80
Installazione	Lampade da incasso
Garanzia	5 years
Peso lordo	2.7 kg
Volume	0.014431 m ³

Info tecniche e installative

Peso netto	2.2 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	NO, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	Separate, included Replaceable (by qualified operators only), electronic
Accessori non inclusi	Dimmable driver, Mounting kit (Suspension kit, Surface kit, Plasterboard recessed frame)



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	40 W
Emissione	Direct
Consumo massimo	max 40,00 W
Caratteristiche LED	LED SMD
CCT LED	4000 K
Durata LED (t. 25°c)	25000 h
CRI	> 80
Fascio luminoso	81°
UGR massimo	< 19
Flusso sorgente	4450 lm
Flusso utile	3550 lm