



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

| | |
|----------------------|---|
| Ean | 8021696189956 |
| Articolo | SMILE TR 3-PHASE 15W CRI80 50° 4000K WH |
| Installazione | Proiettori e Binari |
| Garanzia | 5 years |
| Peso lordo | 0.61 kg |
| Volume | 0.005011 m ³ |

Info tecniche e installative

| | |
|--------------------------------|--|
| Peso netto | 0.61 kg |
| Classe di isolamento | II |
| Grado di protezione | IP20 |
| Conformità | CE |
| Temperatura d'esercizio | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Alimentazione | 220-240 V AC 50/60 Hz |
| Alimentatore | In-built, included Replaceable (by qualified operators only), electronic, tridonic |
| Resistenza al carico | IK06 |
| Accessori non inclusi | Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile |

Info sorgente e prestazionali

| | |
|------------------------------|---|
| Sorgente integrata | Integrated LED module |
| Sorgente sostituibile | Replaceable (by qualified operators only) |
| Potenza | 15 W |
| Emissione | Direct |
| Consumo massimo | max 15 W |
| Caratteristiche LED | LED COB PHILIPS |
| CCT LED | 4000 K |
| Durata LED (t. 25°c) | 50000 h |
| CRI | > 80 |
| SDCM | 3 |
| Fascio luminoso | 50° |
| Flusso sorgente | 2250 lm |
| Flusso utile | 1870 lm |