



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696189673
Articolo	SMILE TR 3-PHASE 20W CRI80 24° 4000K WH
Installazione	Proiettori e Binari
Garanzia	5 years
Peso lordo	0.87 kg
Volume	0.005011 m ³

Info tecniche e installative

Peso netto	0.87 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Resistenza al carico	IK06
Accessori non inclusi	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	20 W
Emissione	Direct
Consumo massimo	max 20 W
Caratteristiche LED	LED COB PHILIPS
CCT LED	4000 K
Durata LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Fascio luminoso	24°
Flusso sorgente	3150 lm
Flusso utile	2660 lm