



## Info generali

### Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

|                      |   |
|----------------------|---|
| <b>Ean</b>           | 8021696189871                           |
| <b>Articolo</b>      | SMILE TR 3-PHASE 30W CRI80 36° 3000K WH |
| <b>Installazione</b> | Proiettori e Binari                     |
| <b>Garanzia</b>      | 5 years                                 |
| <b>Peso lordo</b>    | 0.87 kg                                 |
| <b>Volume</b>        | 0.005011 m <sup>3</sup>                 |

## Info tecniche e installative

|                                |  |
|--------------------------------|--|
| <b>Peso netto</b>              | 0.87 kg  |
| <b>Classe di isolamento</b>    | II   |
| <b>Grado di protezione</b>     | IP20   |
| <b>Conformità</b>              | CE   |
| <b>Temperatura d'esercizio</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>                  | Non-dimmable, On-Off   |
| <b>Alimentazione</b>           | 220-240 V AC 50/60 Hz  |
| <b>Alimentatore</b>            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic             |
| <b>Resistenza al carico</b>    | IK06   |
| <b>Accessori non inclusi</b>   | Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile |

## Info sorgente e prestazionali

|                              |   |
|------------------------------|---|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | 30 W                                      |
| <b>Emissione</b>             | Direct                                    |
| <b>Consumo massimo</b>       | max 30 W                                  |
| <b>Caratteristiche LED</b>   | LED COB PHILIPS                           |
| <b>CCT LED</b>               | 3000 K                                    |
| <b>Durata LED (t. 25°c)</b>  | 50000 h                                   |
| <b>CRI</b>                   | > 80                                      |
| <b>SDCM</b>                  | 3   |
| <b>Fascio luminoso</b>       | 36°                                       |
| <b>Flusso sorgente</b>       | 4000 lm                                   |
| <b>Flusso utile</b>          | 3480 lm                                   |