

Info generali

Interno - Applique


Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission



| | |
|----------------------|------------------------|
| Ean | 8021696158242 |
| Articolo | NORDIK AP2 |
| Installazione | Applique |
| Garanzia | 5 years |
| Peso lordo | 1.16 kg |
| Volume | 0.01058 m ³ |

Info tecniche e installative

| | |
|--------------------------------|--|
| Peso netto | 0.63 kg |
| Classe di isolamento | I |
| Grado di protezione | IP20 |
| Conformità | CE |
| Temperatura d'esercizio | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Alimentazione | 100-240 V AC 50/60 Hz |
| Alimentatore | In-built, included Replaceable (by qualified operators only), electronic |



Info sorgente e prestazionali

| | |
|------------------------------|--|
| Sorgente integrata | Light bulb (not included), Integrated LED module |
| Sorgente sostituibile | Replaceable (LED: by qualified operators only) |
| Potenza | E14/LED max 1 x 40W / 1.5 W |
| Emissione | Diffuse + Direct |
| Consumo massimo | max 40W / LED 1.5 W |
| Caratteristiche LED | LED SMD BRIDGELUX |
| CCT LED | 3000 K |
| Durata LED (t. 25°c) | 20000 h |
| CRI | > 90 |
| SDCM | 3 |
| Fascio luminoso | 23° |
| Flusso sorgente | 100 lm |
| Flusso utile | 80 lm |
| Rischio fotobiologico | 2 |
| Lampadina inclusa | 1 |
| Lampadina consigliata | 101200 E14 SFERA 4W 3000K CRI80 TRASP |