



## Info generali

### Interno - Applique

Indoor wall mounted adjustable lamp with multiple sources, in-built switch, in-built USB port and diffuse and direct light emission

|               |                |
|---------------|----------------|
| Ean           | 8021696174808  |
| Articolo      | BOOK-1 AP NERO |
| Installazione | Applique       |
| Garanzia      | 5 years        |
| Peso lordo    | 2 kg           |
| Volume        | 0.01326 m³     |

## Info tecniche e installative

|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| Peso netto              | 1.57 kg                                                                        |
| Classe di isolamento    | I                                                                              |
| Grado di protezione     | IP20                                                                           |
| Conformità              | CE                                                                             |
| Temperatura d'esercizio | 0° ~ +40 °C                                                                    |
| Dimmer                  | Non-dimmable, On-Off                                                           |
| Alimentazione           | 220-240 V AC 50/60 Hz                                                          |
| Alimentatore            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Info sorgente e prestazionali

|                       |                                                  |
|-----------------------|--------------------------------------------------|
| Sorgente integrata    | Light bulb (not included), Integrated LED module |
| Sorgente sostituibile | Replaceable (LED: by qualified operators only)   |
| Potenza               | G9/LED max 1 x 28W / 3 W                         |
| Emissione             | Diffuse + Direct                                 |
| Consumo massimo       | max 28W / LED 3.0 W                              |
| Caratteristiche LED   | LED SMD                                          |
| CCT LED               | 3000 K                                           |
| Durata LED (t. 25°C)  | 15000 h                                          |
| CRI                   | > 90                                             |
| SDCM                  | 3                                                |
| Flusso sorgente       | 190 lm                                           |
| Flusso utile          | LED 170 lm                                       |
| Rischio fotobiologico | 2                                                |
| Lampadina consigliata | 305486 G9 4.0W 3000K CRI80                       |