



Info generali

Interno - Lampade da soffitto

Indoor ceiling mounted projector with integrated LED sources and direct light emission

Ean	8021696206028
Articolo	NITRO PL D07 SQUARE NERO 3000K
Installazione	Lampade da soffitto
Garanzia	5 years
Peso lordo	0.45 kg
Volume	0.001128 m ³

Info tecniche e installative

Peso netto	0.4 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	LED 15 W
Emissione	Direct
Consumo massimo	max 15 W
Caratteristiche LED	LED COB BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	36°
Flusso sorgente	1400 lm
Flusso utile	1220 lm
Rischio fotobiologico	1
Lampadina inclusa	1
Lampadina consigliata	LED INTEGRATO 1400Lm 3000K