

**Info generali****Interno - Applique**

Indoor wall mounted adjustable lamp with multiple integrated LED sources, in-built switches and direct light emission



|                      |                        |
|----------------------|------------------------|
| <b>Ean</b>           | 8021696345482          |
| <b>Articolo</b>      | BONNE NUIT-2 AP NICKEL |
| <b>Installazione</b> | Applique               |
| <b>Garanzia</b>      | 5 years                |
| <b>Peso lordo</b>    | 0.46 kg                |
| <b>Volume</b>        | 0.00175 m³             |

**Info tecniche e installative**

|                                |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| <b>Peso netto</b>              | 0.36 kg                                                                        |
| <b>Classe di isolamento</b>    | II                                                                             |
| <b>Grado di protezione</b>     | IP20                                                                           |
| <b>Conformità</b>              | CE                                                                             |
| <b>Temperatura d'esercizio</b> | 0° ~ +40 °C                                                                    |
| <b>Dimmer</b>                  | Non-dimmable, On-Off                                                           |
| <b>Alimentazione</b>           | 220-240 V AC 50/60 Hz                                                          |
| <b>Alimentatore</b>            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

**Info sorgente e prestazionali**

|                              |                                           |
|------------------------------|-------------------------------------------|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | LED 6,5 W                                 |
| <b>Emissione</b>             | Direct                                    |
| <b>Consumo massimo</b>       | max 6,5 W                                 |
| <b>Caratteristiche LED</b>   | LED SMD CREE                              |
| <b>CCT LED</b>               | 3000 K                                    |
| <b>Durata LED (t. 25°C)</b>  | 50000 h                                   |
| <b>CRI</b>                   | > 90                                      |
| <b>SDCM</b>                  | 3                                         |
| <b>Flusso sorgente</b>       | 420 lm                                    |
| <b>Flusso utile</b>          | 340 lm                                    |
| <b>Rischio fotobiologico</b> | 2                                         |
| <b>Lampadina inclusa</b>     | 1                                         |
| <b>Lampadina consigliata</b> | LED INTEGRATO 420lm 3000K                 |