

Info generali

Interno - Applique


Indoor wall mounted adjustable lamp with multiple integrated LED sources, in-built switches and direct light emission



Ean	8021696345505
Articolo	BONNE NUIT-2 AP OTTONE
Installazione	Applique
Garanzia	5 years
Peso lordo	0.46 kg
Volume	0.001629 m ³

Info tecniche e installative

Peso netto	0.36 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	LED 6,5 W
Emissione	Direct
Consumo massimo	max 6,5 W
Caratteristiche LED	LED SMD CREE
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Flusso sorgente	420 lm
Flusso utile	340 lm
Rischio fotobiologico	2
Lampadina inclusa	1
Lampadina consigliata	LED INTEGRATO 420Lm 3000K